



Code	LG9228MB-RCD
Description	13A RCD Fused Connection Unit - Passive/Latching - Unswitched
Size	87mm x 87mm x 50mm depth
Range	Selectric Metal Clad
Colour	Grey with white insert
Material	High grade steel with aluminium epoxy powder coating
Included	Back box & M3.5 fixing screws
Weight	0.42kg
Inner Carton Quantity	10
Inner Carton Weight	4.2kg
Guarantee	5 years
Barcode	5025117980361
Commodity Code	8539 319090
Standards	BS 1363-2 & BS 61543
Notes	<ul style="list-style-type: none"> • A Fused Spur or Connection Unit is commonly used for powerful electrical appliances, such as washing machines, dish washers, extractor fans, hand dryers etc, that need to be installed without a plug. They are also used for electrical items that need to be installed on a separate cable from the ring main, for safety and maintenance purposes • Surface mounting box included • RCD (residual current device): RDCs are life-saving devices which are designed to prevent you from getting a fatal electric shock if you touch something live, such as a bare wire • LATCHING or PASSIVE: When the power is lost due to an earth fault, the RCD trips out and isolates the circuit it is protecting. Latching RCD's do not trip during power cuts so they are great for fridges, freezers, fish tanks, battery charging and also for protecting remote/unmanned areas • Surface mounting box included